




# SUNTUF® EZ-Glaze

Glass-Like Profiled Polycarbonate sheet



## Overview

SUNTUF® EZ-Glaze offers smart design, elegant glass-like appearance, versatility, low maintenance and sustainable performance.

SUNTUF® EZ-Glaze incorporates a proprietary profiled design which enables it to be installed over rafters with a high loading capacity.

SUNTUF® EZ-Glaze is easy to fasten; the panels are simply screw fixed to the supportive structure and joined by overlapping.

## Main Benefits

- Clear and elegant appearance
- Easy, fast and safe installation
- Minimal maintenance
- UV Protection - blocks 99.9% of UV radiation
- Greater hail resistance
- High wind and snow load resistance

## Typical Applications


- Pergolas and Gazebos
- Patio enclosures
- Sunrooms
- Carports




[www.palram.com](http://www.palram.com)



## Installation Drawing



## Typical Assembly



## Product Availability

|                |                              |                    |        |
|----------------|------------------------------|--------------------|--------|
| Colors         | Grey   Bluish Breeze   Clear |                    |        |
| Thickness      | 3 mm                         |                    |        |
| Cover Width    | 600 mm                       | <b>Total Width</b> | 673 mm |
| Maximum Length | 7,000 mm                     |                    |        |

\* Maximum recommended single unit length is 7,000mm

## Solar Properties

|               | LT (%) | SC*  | SHGC** |
|---------------|--------|------|--------|
| Clear         | 90     | 1.0  | 0.87   |
| Grey          | 20     | 0.51 | 0.44   |
| Bluish Breeze | 70     | 0.63 | 0.55   |

\*Shading Coefficient

\*\*Solar Heat Gain (SHGC)

## Loads Resistance

Wind Uplift: 2.0 Kpa

Wind Load: 4.0 Kpa

Tested to comply with AS4040.1

\*Please Note "Ultimate Wind pressure based on Regions A & B using standard polycarbonate screw fasteners. Please contact Palram Representative if higher pressures are required"

## Flammability

SUNTUF® EZ-Glaze complies with the most demanding international fire standards in the field of plastic.

- AS9705- Group 1 AS1530.3- Ignitability- 0, Spread of Flame- 0, Heat Index- 0, Smoke- 2.

\*For more detailed information please contact your Palram distributor.



**PALRAM SA/NT**  
517A Cross Keys Road  
Cavan SA 5094  
Tel: (08) 8262 2288  
Fax: (08) 8262 3388  
salesa@palram.com

**PALRAM NSW/ACT**  
Unit 2, 26 Redfern St.  
Wetherill Park, NSW 2164  
Tel: (02)8788 6100  
Fax: (02) 8788 6199  
salesnsw@palram.com

**PALRAM QLD**  
Unit 9C / 380 Bilsen Road  
Geebung QLD 4034  
Tel: (07) 3172 5581  
Fax: (07) 3172 5516  
salesqld@palram.com

**PALRAM VIC/TAS**  
34 Buys Court  
Derrimut VIC 3030  
Tel: (03) 9219 4444  
Fax: (03) 9219 4455  
salesvic@palram.com

**PALRAM WA**  
74 Christable Way  
Landsdale WA 6065  
Tel: (08) 9302 4173  
Fax: (08) 9302 5287  
saleswa@palram.com



87733 - 10/2021

In as much as Palram Industries has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the material's suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be construed as constituting a license under any Palram Industries patent covering such use or as recommendations for use of such materials in the infringement of any patent. Palram Industries or its distributors cannot be held responsible for any losses incurred through incorrect installation of the material. In accordance with our company policy of continual product development you are advised to check with your local Palram Industries supplier to ensure that you have obtained the most up to date information.

